

COSHH 2002 reg 6: exposure is assessed BEFORE the work starts; reg 7: it is prevented, or adequately controlled, working down the hierarchy — eliminate, substitute, engineer, then RPE last. This assessment covers the substance family below; it is completed against the actual products (their safety data sheets alongside) and the actual task, and briefed to the people exposed. The current workplace exposure limit, where one applies, comes from EH40 and the SDS on the day — write it in below.

1 ASSESSMENT DETAILS

SITE / PROJECT

TASK ASSESSED

PRODUCTS IN USE (SDS TO HAND)

ASSESSED BY

DATE

2 THE SUBSTANCE — WHAT IT IS AND WHAT IT DOES

WHERE IT IS MET: Spraying and brushing release agents onto formwork, shutters and precast moulds before concrete pours, and cleaning formwork afterwards. Spray application makes a mist; the oils defat skin.

THE HARM: Mineral oil mist irritates airways and prolonged skin contact causes dermatitis and oil acne; some release agents are solvent-based and add vapour and flammability. Slippery residues on decks and ladders cause falls.

3 EXPOSURE — ROUTES, PEOPLE, LIMIT

Inhalation — dust, fume, vapour or mist

Ingestion — hand to mouth

Skin and eye contact

Others affected — adjacent trades, occupiers, public

WHO IS EXPOSED, HOW LONG, HOW OFTEN

WEL / LIMIT (FROM EH40 AND THE SDS TODAY)

4 CONTROLS — IN THE REG 7 HIERARCHY, ALL IN PLACE BEFORE WORK STARTS

Water-based or vegetable-oil release agents substituted where the finish specification allows

Brush or roller in preference to spray; spray application with the RPE the SDS names and other trades out of the mist

Nitrile gloves, sleeves and eye protection; oil-soaked clothing changed

Applied surfaces and walkways treated as slippery — access boards kept clean

Drips and over-spray contained; nothing to drains or ground

SITE-SPECIFIC CONTROLS FOR THIS TASK

RPE WORN (TYPE, AND FACE-FIT WHERE TIGHT-FITTING)

OTHER PPE FOR THIS SUBSTANCE

5 HEALTH SURVEILLANCE, HYGIENE AND FIRST AID

Skin checks for regular users; dermatitis investigated.

6 STORAGE, SPILLAGE AND DISPOSAL

Drums banded, away from heat and drains; spill kit at the point of use.

WHERE IT IS STORED ON THIS SITE

SPILL RESPONSE AT THE WORK

7 SIGN-OFF AND BRIEFING

The assessment is complete when the people exposed have been briefed on it. Reassess when the product, task, quantity or location changes — not on an anniversary.

ASSESSOR — PRINTED NAME

SIGNATURE

DATE

WORKFORCE BRIEFED (DATE / RECORD REF)

R REVISION HISTORY

Every revision of this document, and every review that found nothing to change. The revision on the front of this sheet is the one you are holding — check kubitdocs.com for the current one before use.

Rev	Date	Class	What changed	Authorised by
D0	2026-09-01	first-issue	First issue.	— not yet approved —
A0	2026-09-01	review	Approved for issue by the author. Content unchanged from the reviewed draft; the draft status strip is removed. No independent third-party review has been carried out.	Author — director, UK principal contractor, SMSTS. Not an independent review.

Class: first-issue · material (the law, a control, a field or the scope changed — past buyers are notified) · editorial (wording or layout only) · review (checked, nothing changed) · withdrawal. Revision prefix D = draft, not approved and not for sale; A = approved for issue by the person named, on the date shown.